

# PRODUCT SUBMITTAL

WIRE-BOND

## QUIK SET SEALANT



### DESCRIPTION:

QUIK SET Sealant is a fast grab adhesive and sealant using innovative hybrid technology, a silane-terminated polyether (STPE). It is a non-shrinking 100% solids adhesive, free of solvents and which will skin over 10-15 minutes and a full cure in 4-7 days depending on temperature and relative humidity.

### USES:

Can be applied to concrete, brick, stone, metal, wood, EPDM, EPS, Styrofoam insulation, PVC, plastics and other construction materials. Used as a seal on horizontal and vertical seams, overlaps, punctures and other terminations such as end dams or protrusions. Also, as a spot adhesive during application of a material.

**PACKAGING:** Available in 10.2 oz. cartridges

### TECHNICAL DATA

Viscosity	Non-slump gun grade	1,800,000 cps (spindle 7, 4rpm)
Skin Formation Time		10 minutes @ 70°F, 50% RH
Hardness	<b>ASTM C661</b>	45Shore A
Tensile Strength	<b>ASTM D412</b>	1.42 MPa
Density	<b>ASTM D1475</b>	14.8 Lbs./Gal.
Elongation at Break	<b>ASTM D412</b>	150%
Service Temperature		-50°F- 220°F
Exposure		6 Months
Appearance		White

**Corporate Office:** 400 Rountree Rd Charlotte, NC 28217 TEL:  
(800) 849-6722 FAX: (704) 525-3761

**Mailing Address:** P.O. Box 240988 Charlotte, NC 28224



[www.wirebond.com](http://www.wirebond.com)

**Memphis Plant:** 2365 Harbor Ave. Memphis, TN 38113  
TEL: (800) 441-8359 FAX: (901) 775-9449

**Mailing Address:** P.O. Box 13124 Memphis, TN 38113